

**Battery powered plastic strapping tools for heavy strapping**

---



**Characteristics**

---

Strapping qualities:	Polypropylene (PP) and Polyester (PET)	
Strapping dimensions:	widths	19.0 – 25.0 mm / 3/4 – 1"
	thicknesses	0.40 – 1.53 mm / .016 – .060"
Weight incl. battery:	5.7 kg / 12.6 lbs	
Tool sizes with battery:	L395 x W137 x H143 mm / 14" x 5" x 5"	
Average seal strength:	up to 75% (dependent on strap quality)	
Type of seal:	Friction weld sealing	
Strap tension:	1200 – 6000 N / 270 – 1350 lbs (adjustable)	
Tensioning speed:	70 – 87 mm/s / 2.8 – 3.4 inch/s	
Power supply:	Battery	28VDC / 3.0 Ah Li-Ion
Suspension bracket (optional)		

**Advantages**

---

- Ergonomic design with small handle
- Well balanced tool for all strapping positions
- Simple one-handed operation
- Exceptional tension force
- Sealing time adjustable
- Easy strap threading; Both straps are inserted together
- Welding lever locks in bottom position and allows the preparation of the next strapping during welding and cooling
- Tools welds without tension (strap repair)
- Quick battery exchange
- Latest Li-Ion battery technology

Distributed By:  
**Allstrap**  
1719 Kenny Rd  
Columbus, OH, 43212

**Chart of types model P330**

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.0254	P330/19/0.80-1.19	19	3/4	0.80-1.19	.031-.047	6000	1350	70-87	2.8-3.4
43.0256	P330/19/1.20-1.53	19	3/4	1.20-1.53	.047-.060	6000	1350	70-87	2.8-3.4
43.0262	P330/25/0.40-0.79	25	1	0.40-0.79	.016-.031	6000	1350	70-87	2.8-3.4
43.0264	P330/25/0.80-1.19	25	1	0.80-1.19	.031-.047	6000	1350	70-87	2.8-3.4
43.0266	P330/25/1.20-1.35	25	1	1.20-1.35	.047-.053	6000	1350	70-87	2.8-3.4

**Battery chargers for model P330**

Item No.	Model	Charging type	Tension	Countries
N5.4435	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, Z, ZA, ZW
N5.4437	Battery standard charger	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4439	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4441	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	AUS, NZ

**Replacement battery for model P330**

Item No.	Model	Tension	Power
N5.4326	Accu Li-Ion	28VDC	3.0 Ah

**Accessories**

P32.0112	Standard suspension bracket
P33.0120	Suspension bracket for alternating positions
P33.0121	Wearing sheet for rough surfaces
P33.0122	Wearing plate for rough surfaces
P32.2061	Turning button kit

Distributed By:  
**Allstrap**  
 1719 Kenny Rd  
 Columbus, OH, 43212