

Order from Allstrap 866-779-2673



Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

A338

***Manual sealless steel strapping tool
for high tension***



A338

Manual sealless steel strapping tool for high tension

Strapping qualities	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi	
Strapping dimensions:	widths	12.7 – 19.0 mm / 1/2 - 3/4"
	thicknesses	0.50 – 0.70 mm / .020 – .028"
Weights	5.7 kg / 12.6 lbs Normal-version 5.9 kg / 13.0 lbs TW-version	
Average seal strength	approx. 80 %	
TW-version available	Torque wrench tensioning system	
Suspension (optional)	Suspension bracket for vertical- and horizontal applications; has to be ordered separately, see accessories Handle for horizontal applications; has to be ordered separately	

The advantages

- the special tensioning gear-system allows a high strap tension of up to 5'500 N (1240 lbs) with a limited amount of tensioning effort of only 240 N (54 lbs)
- handy sealless combination tool to strap flat packages (e.g. pallets, bales, crates, cases, various packages)
- permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- the sealless joint reduces the overall strapping costs by approx. 10 % through the elimination of the seals

Chart of types Model A338

Item. No.	Model	Width		Ultraflex max. 850 N/mm ² /123.000 psi		Thickesses		Ultraflex max. 1100 N/mm ² /160.000 psi	
		mm	inch	mm	inch	mm	inch	mm	inch
13.2910	A338/12.7/0.50-0.64	12.7	1/2"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2915	A338/12.7/0.70/UNI	12.7	1/2"	0.70	.028	—	—	—	—
13.2920	A338/13/0.50-0.64	13		0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2925	A338/13/0.70/UNI	13		0.70	.028	—	—	—	—
13.2930	A338/16/0.50-0.64	16	5/8"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2935	A338/16/0.70/UNI	16	5/8"	0.70	.028	—	—	—	—
13.2940	A338/19/0.50-0.64	19	3/4"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2945	A338/19/0.70/UNI	19	3/4"	0.70	.028	—	—	—	—
13.2911	A338/12.7/0.50-0.64/TW	12.7	1/2"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2916	A338/12.7/0.70/UNI/TW	12.7	1/2"	0.70	.028	—	—	—	—
13.2921	A338/13/0.50-0.64/TW	13		0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2926	A338/13/0.70/UNI/TW	13		0.70	.028	—	—	—	—
13.2931	A338/16/0.50-0.64/TW	16	5/8"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2936	A338/16/0.70/UNI/TW	16	5/8"	0.70	.028	—	—	—	—
13.2941	A338/19/0.50-0.64/TW	19	3/4"	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025	0.50 – 0.64	.020 – .025
13.2946	A338/19/0.70/UNI/TW	19	3/4"	0.70	.028	—	—	—	—

UNI = Uniflex, Regular duty strapping max. 850 N/mm² / 123'000 psi ■ ULT = Ultraflex, High tensile strapping max. 1100 N/mm² / 160'000 psi ■ TW = Torque wrench tensioning system



Accessories

Item. No.	Description
A33.5301	Suspension bracket for vertical- and horizontal application
A33.5307	Handle for horizontal applications