

Order from Allstrap 866-779-2673



Distributed By:
Allstrap

1719 Kenny Rd
Columbus, OH, 43212

A384
*Pneumatic sealless steel
strapping tool*



Order from Allstrap 866-779-2673



Oil reservoir
The large refilling reservoir allows easy servicing.



Strap tension regulation
Through simple regulation the strap tension can be adapted individually to every type of package.



Releasing of the feed wheel
In case of a faulty operation of the tool the feed wheel can be released from the jammed strap by removing the air motor.



Sealless joint
The consistency of the seal efficiency of the sealless joint is very high and as a general rule it is higher than joints using a separate seal. Cost savings around 10 % of the overall strapping costs can be achieved by the use of sealless strapping tools.



Applications
An ideal tool for a variety of standard, vertical and horizontal applications in practically all industries.

Distributed By:
Allstrap
1719 Kenny Rd
Columbus, OH, 43212

Chart of types Model A384

Item No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi				Tension in		Tension speed	
		Width		Thicknesses		N	lbs	mm/s	inch/s
		mm	inch	mm	inch				
13.6810	A384/9.5/0.38-0.50/3.5	9.5	3/8"	0.38 - 0.50	.015 - .020	3500	780	105	4.1
13.6811	A384/9.5/0.38-0.50/2.2	9.5	3/8"	0.38 - 0.50	.015 - .020	2200	495	165	6.5
13.6820	A384/10/0.38-0.50/3.5	10.0		0.38 - 0.50	.015 - .020	3500	780	105	4.1
13.6821	A384/10/0.38-0.50/2.2	10.0		0.38 - 0.50	.015 - .020	2200	495	165	6.5
13.6830	A384/12.7/0.38-0.50/3.5	12.7	1/2"	0.38 - 0.50	.015 - .020	3500	780	105	4.1
13.6831	A384/12.7/0.38-0.50/6.5	12.7	1/2"	0.38 - 0.50	.015 - .020	6500	1460	60	2.3
13.6832	A384/12.7/0.58-0.63/3.5	12.7	1/2"	0.58 - 0.63	.015 - .025	3500	780	105	4.1
13.6833	A384/12.7/0.58-0.63/6.5	12.7	1/2"	0.58 - 0.63	.015 - .025	6500	1460	60	2.3
13.6834	A384/12.7/0.38-0.50/2.2	12.7	1/2"	0.38 - 0.50	.015 - .020	2200	495	165	6.5
13.6835	A384/12.7/0.38-0.50/4.1	12.7	1/2"	0.38 - 0.50	.015 - .020	4100	920	95	3.7
13.6836	A384/12.7/0.58-0.63/2.2	12.7	1/2"	0.58 - 0.63	.015 - .025	2200	495	165	6.5
13.6837	A384/12.7/0.58-0.63/4.1	12.7	1/2"	0.58 - 0.63	.015 - .025	4100	920	95	3.7
13.6840	A384/13/0.38-0.50/3.5	13.0		0.38 - 0.50	.015 - .020	3500	780	105	4.1
13.6841	A384/13/0.38-0.50/6.5	13.0		0.38 - 0.50	.015 - .020	6500	1460	60	2.3
13.6842	A384/13/0.58-0.63/3.5	13.0		0.58 - 0.63	.015 - .025	3500	780	105	4.1
13.6843	A384/13/0.58-0.63/6.5	13.0		0.58 - 0.63	.015 - .025	6500	1460	60	2.3
13.6844	A384/13/0.38-0.50/2.2	13.0		0.38 - 0.50	.015 - .020	2200	495	165	6.5
13.6845	A384/13/0.38-0.50/4.1	13.0		0.38 - 0.50	.015 - .020	4100	920	95	3.7
13.6846	A384/13/0.58-0.63/2.2	13.0		0.58 - 0.63	.015 - .025	2200	495	165	6.5
13.6847	A384/13/0.58-0.63/4.1	13.0		0.58 - 0.63	.015 - .025	4100	920	95	3.7
13.6850	A384/16/0.38-0.50/3.5	16.0	5/8"	0.38 - 0.50	.015 - .020	3500	780	105	4.1
13.6851	A384/16/0.38-0.50/6.5	16.0	5/8"	0.38 - 0.50	.015 - .020	6500	1460	60	2.3
13.6852	A384/16/0.58-0.63/3.5	16.0	5/8"	0.58 - 0.63	.015 - .025	3500	780	105	4.1
13.6853	A384/16/0.58-0.63/6.5	16.0	5/8"	0.58 - 0.63	.015 - .025	6500	1460	60	2.3
13.6854	A384/16/0.38-0.50/2.2	16.0	5/8"	0.38 - 0.50	.015 - .020	2200	495	165	6.5
13.6855	A384/16/0.38-0.50/4.1	16.0	5/8"	0.38 - 0.50	.015 - .020	4100	920	95	3.7
13.6856	A384/16/0.58-0.63/2.2	16.0	5/8"	0.58 - 0.63	.015 - .025	2200	495	165	6.5
13.6857	A384/16/0.58-0.63/4.1	16.0	5/8"	0.58 - 0.63	.015 - .025	4100	920	95	3.7
13.6860	A384/19/0.50-0.63/3.5	19.0	3/4"	0.50 - 0.63	.015 - .025	3500	780	105	4.1
13.6861	A384/19/0.50-0.63/6.5	19.0	3/4"	0.50 - 0.63	.015 - .025	6500	1460	60	2.3
13.6862	A384/19/0.50-0.63/2.2	19.0	3/4"	0.50 - 0.63	.015 - .025	2200	495	165	6.5
13.6863	A384/19/0.50-0.63/4.1	19.0	3/4"	0.50 - 0.63	.015 - .025	4100	920	95	3.7
13.6870	A384/20/0.50-0.63/3.5	20.0		0.50 - 0.63	.015 - .025	3500	780	105	4.1
13.6871	A384/20/0.50-0.63/6.5	20.0		0.50 - 0.63	.015 - .025	6500	1460	60	2.3
13.6872	A384/20/0.50-0.63/2.2	20.0		0.50 - 0.63	.015 - .025	2200	495	165	6.5
13.6873	A384/20/0.50-0.63/4.1	20.0		0.50 - 0.63	.015 - .025	4100	920	95	3.7

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

Distributed By:
Allstrap

1719 Kenny Rd
 Columbus, OH, 43212

