

Order from Allstrap 866-779-2673

SEALLESS STEEL STRAPPING COMBINATION

Model ASC-20 for HT and RD Steel Strapping



- For use with 1/2" x .020 to 3/4" x .025 (12 x 0.5 to 19 x 0.7mm) RD or HT strapping
- Original design based on 15 years of worldwide field use and feedback
- Light weight of 8.5 lbs. and small footprint
- Easiest sealless combination tool to operate, adjust and maintain
- Reversible dies for double life and 1/3 of replacement cost
- Designed to minimize damage from accidental drops
- Lifetime availability of parts and service
- 90 day parts and labor written guarantee

- For use with:
 - RD Strapping: 1/2" x .015 to 3/4" x .023 (12 x 0.4 to 19 x 0.63mm)
 - HT Strapping: 1/2" to 3/4" x up to .020 (12 to 19mm x up to 0.5mm)
- Very lightweight - 7.5 lbs.
- Inexpensive and easy to operate, adjust and maintain
- Reversible dies for double life and 1/3 of replacement cost
- Simple, ergonomic design minimizes operator fatigue
- Lifetime availability of parts and service
- 90-day parts and labor written guarantee

Model ASC-16 for RD and HT Steel Strapping



Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212