

Purchase from Allstrap  
(866) 779-2673

# Semi-Auto Pallet Strapping Machine

**TP-502MH Genesis Hori**

**TP-502MV Genesis Verti**

TP-502MH (horizontal strapping) and TP-502MV (vertical strapping) inherit all of the advantages from **TP-502 Genesis**, such as compact strapping head, direct drive technology with German-made DC motors and electronic tension control. They can be moved easily beside the load you want to strap; no need to move the pallet. The TP-502MH and TP-502MV are quick, ergonomic, and economic solution for low volume horizontal and vertical strapping.



**new**

*Tension force*  
*Up to 70 kg*



\*Pictures shown with battery option

# TP-502MH Genesis Hori (horizontal strapping)

## Main Features

- ▶ **Various Applications**  
Suitable for fruit & vegetable boxes, concrete blocks, and pallet loaded with cardboard boxes containing any type of products.
- ▶ **Adjustable Strapping Height**  
The strapping height is quickly and effortlessly adjustable from 180 mm to 2200 mm above the floor.
- ▶ **Weld-Cooling Timer**  
The weld cooling time can be increased to insure high joint efficiency under high tension.
- ▶ **Two moving direction**  
With simple adjustment, the machine can be moved either forward or sideward to approach the pallet.
- ▶ **Casters with brake to prevent unwanted movements.**

## Options

- ▶ **Battery power supply (TP-502MHB)**
- ▶ **Edge protector holder**



### Technical Data

Strap Type: PP strap  
Strap Width: 9 mm-15.5 mm  
Strap Tension: 8 kg-70 kg  
Net Weight: 242 kg  
Electrical Requirement:  
110V, 220V, 230V 50/60Hz 1PH

# TP-502MV Genesis Verti (vertical strapping)

## Main Features

- ▶ **Various Applications**  
Suitable for corrugated cardboards, concrete blocks, and pallet loaded with cardboard boxes containing any type of products.
- ▶ **Weld-Cooling Timer**  
The weld cooling time can be increased to insure high joint efficiency under high tension.
- ▶ **Good for Lower Height Pallet**  
Enable to strap pallet with height as low as 380 mm.

## Option

- ▶ **Battery power supply (TP-502MVB)**



### Technical Data

Strap Type: PP strap  
Strap Width: 9 mm-15.5 mm  
Strap Tension: 8 kg-70 kg  
Net Weight: 81 kg  
Electrical Requirement:  
110V, 220V, 230V 50/60Hz 1PH

All specifications are subject to change without notice.

**Purchase from Allstrap**  
**(866) 779-2673**