

Manual sealless steel strapping tool for high tension

**Characteristics**

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 12.7 – 19.0 mm / ½ – ¾"
thicknesses	0.50 – 0.70 mm / .020 – .028"
Weights:	5.7 kg / 12.6 lbs Normal-version 5.9 kg / 13.0 lbs TW-version
Average seal strength:	approx. 80 %
Versions available:	Torque wrench tensioning system MicroLock™ system
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately Handle for horizontal applications; has to be ordered separately

Advantages

- The special tensioning gear-system allows a high strap tension of up to 5500 N (1240 lbs) with a limited amount of tensioning effort of only 240 N (54 lbs)
- Handy sealless combination tool to strap flat packages (e.g. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- The MicroLock™ sealless system guarantees a maximum of security of the sealless steel strapping joint against unlocking

Distributed By:

Allstrap1719 Kenny Rd
Columbus, OH, 43212

Chart of types model A338

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2910	A338/12.7/0.50-0.64	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2911	A338/12.7/0.50-0.64/TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2915	A338/12.7/0.70/UNI	12.7	1/2"	0.70	.028	-	-
13.2916	A338/12.7/0.70/UNI/TW	12.7	1/2"	0.70	.028	-	-
13.2920	A338/13/0.50-0.64	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2921	A338/13/0.50-0.64/TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2925	A338/13/0.70/UNI	13		0.70	.028	-	-
13.2926	A338/13/0.70/UNI/TW	13		0.70	.028	-	-
13.2930	A338/16/0.50-0.64	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2931	A338/16/0.50-0.64/TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2935	A338/16/0.70/UNI	16	5/8"	0.70	.028	-	-
13.2936	A338/16/0.70/UNI/TW	16	5/8"	0.70	.028	-	-
13.2940	A338/19/0.50-0.64	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2941	A338/19/0.50-0.64/TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2945	A338/19/0.70/UNI	19	3/4"	0.70	.028	-	-
13.2946	A338/19/0.70/UNI/TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

TW = Torque wrench tensioning system

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

Chart of types model A338 with MicroLock™

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2950	A338/12.7/0.50-0.64/ML	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2951	A338/12.7/0.50-0.64/ML /TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2955	A338/12.7/0.70/UNI/ML	12.7	1/2"	0.70	.028	-	-
13.2956	A338/12.7/0.70/UNI/ML /TW	12.7	1/2"	0.70	.028	-	-
13.2960	A338/13/0.50-0.64/ML	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2961	A338/13/0.50-0.64/ML /TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2965	A338/13/0.70/UNI/ML	13		0.70	.028	-	-
13.2966	A338/13/0.70/UNI/ML /TW	13		0.70	.028	-	-
13.2970	A338/16/0.50-0.64/ML	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2971	A338/16/0.50-0.64/ML /TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2975	A338/16/0.70/UNI/ML	16	5/8"	0.70	.028	-	-
13.2976	A338/16/0.70/UNI/ML /TW	16	5/8"	0.70	.028	-	-
13.2980	A338/19/0.50-0.64/ML	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2981	A338/19/0.50-0.64/ML /TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2985	A338/19/0.70/UNI/ML	19	3/4"	0.70	.028	-	-
13.2986	A338/19/0.70/UNI/ML /TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

TW = Torque wrench tensioning system

ML= MicroLock™

Accessories

- A33.5301 Suspension for vertical and horizontal applications
- A33.5307 Handle for horizontal applications

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212