

Pneumatic pusher type combination steel strapping tool

**Characteristics**

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	width 19.0 mm / ¾"
	thicknesses 0.63 – 0.90 mm / .025-.035"
Weights:	6.5 kg / 14.3 lbs without suspension 7.0 kg / 15.4 lbs with suspension
Average seal strength:	approx. 75 %
Seals:	Overlap seals, see chart
Type of joint:	Double notch upcut joint
Strap tension:	The tool is available for two different stages for strap tension, see charts
Suspension:	Universal suspension bracket is supplied with the tool

Advantages

- Ideal high performance strapping tool for metal products i.e. coils, loads of bars, pipes, bundles, rods and curved or irregularly shaped packages
- The perfect double notch upcut joint is accomplished in a single operation
- The low weight of the tool allows a mobile operation without any suspension system

Distributed By:

Allstrap1719 Kenny Rd
Columbus, OH, 43212

Chart of types model A482

Item No.	Model	Uniflex Regular duty strapping max. 850 N/mm ² / 123'000 psi				Max. Tension		Tension speed	
		Width		Thicknesses		N	lbs	mm/s	inch/s
		mm	inch	mm	inch				
13.4630	A482/19/0.70-.90/UNI/4.0	19	3/4"	0.70-0.90	.027-.035	4000	900	125	4.9
13.4640	A482/19/0.70-.90/UNI/7.0	19	3/4"	0.70-0.90	.027-.035	7000	1570	70	2.7

Item No.	Model	Ultraflex High tensile strapping max. 1100 N/mm ² / 160'000 psi				Max. Tension		Tension speed	
		Width		Thicknesses		N	lbs	mm/s	inch/s
		mm	inch	mm	inch				
13.4610	A482/19/0.63-.80/ULT/4.0	19	3/4"	0.63-0.80	.025-.031	4000	900	125	4.9
13.4620	A482/19/0.80/ULT/7.0	19	3/4"	0.80	.031	7000	1570	70	2.7

UNI = Uniflex
ULT = Ultraflex

Recommended seals

Width mm	Inch	Dimensions (W, L, T)	
		mm	inch
19	3/4"	19 x 45 x 0.9	-

Tensile strength of the seal material: 600 N/mm² / 87'000 psi

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212