

Battery powered plastic strapping tools

**Characteristics**

Strapping qualities:	Polypropylene (PP) and Polyester (PET)	
Strapping dimensions:	widths	10.0 – 16.0 mm / 3/8 – 5/8"
	thicknesses	0.40 – 1.05 mm / .016 – .041"
Weight incl. battery:	3.95 kg / 8.7 lbs	
Tool sizes with battery:	L350 x W122 x H130 mm / 13.8" x 4.8" x 5.1"	
Average seal strength:	up to 75% (dependent on strap quality)	
Type of seal:	Friction weld sealing	
Strap tension:	400 – 2400 N / 90 – 540 lbs (adjustable)	
Tensioning speed:	85 – 190 mm/s / 3.3 – 7.5 inch/s	
Power supply:	Battery	18VDC / 3.0 Ah Li-Ion
Suspension bracket (optional)		

Advantages

- Complies with the European Safety Regulations EN 415-8
- New reinforced 18V motor
- Li-Ion battery technology
- Very high capacity of up to 600 strap cycles per battery load (dependent on strap quality and dimension)
- Battery protection
- Simple one-handed operation
- Very high tension force with adjustable tension speed
- Tension force and sealing time adjustable

Distributed By:

Allstrap

1719 Kenny Rd

Columbus, OH, 43212

Chart of types model P326

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2201	P326/10/0.4-0.64	10.0	3/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2202	P326/10/0.65-1.05	10.0	3/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2211	P326/11.1/0.4-0.64	11.1	7/16"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2212	P326/11.1/0.65-1.05	11.1	7/16"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2221	P326/12/0.4-0.64	12		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2222	P326/12/0.65-1.05	12		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2223	P326/12.7/0.4-0.64	12.7	1/2"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2224	P326/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2231	P326/13/0.4-0.64	13		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2232	P326/13/0.65-1.05	13		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2251	P326/15/0.4-0.64	15		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2252	P326/15/0.65-1.05	15		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2253	P326/15.5/0.4-0.64	15.5		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2254	P326/15.5/0.65-1.05	15.5		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2261	P326/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2262	P326/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5

Battery chargers for model P326

Item No.	Model	Charging type	Tension	Countries
N5.4443	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Battery standard charger	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter required

Battery for model P326

Item No.	Model	Tension	Power
N5.4330	Accu Li-Ion	18VDC	3.0 Ah

Accessories

P32.0112	Standard suspension bracket
P32.0137	Suspension bracket for alternating positions

Distributed By:

Allstrap

1719 Kenny Rd

Columbus, OH, 43212