

StrapPack[®]

Semi Automatic Strapping Machine



JK-2

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

JK-2

Innovative Semi Automatic Strapping Machine

■ Automatic Feed Length

The JK-2 records the length of strap required and feeds exactly the same length automatically for every package. The operator resets the feed length memory and pulls the strap to the length needed. Exactly the same length of strap will be fed on the following cycles.

■ Adjustable Table Height

The table height can be easily adjusted from 750mm (30") to 850mm (33 1/2") in 20mm (3/4") increments.

■ Capable of Soft Tension

The JK-2 has soft tension capability and can strap fragile packages without creating any damage.

■ Easy Strap Width Conversion

Changing the strap width is very easy. You can use from 5mm to 15.5 mm (5/8") polypropylene strap. No additional parts are required.

■ Sturdy Body yet Quiet Operation

The JK-2 is solid and durable, manufactured with quality materials, and it is amazingly quiet. The large tabletop provides ample workspace.

■ Easy Maintenance

The JK-2 has less moving parts than any other strapping machines of its kind, which can save operating cost and simplify the maintenance. In addition, Strapack has developed a new, unique maintenance mode on this machine. When engaged, the JK-2 steps through the strapping cycle one operation at a time. By observing the operation of the JK-2 in this special mode, it is easy to identify problems and make adjustments. Diagnosing problems has never been easier!

Standard Specifications

Dimensions	Width	870mm	34-1/4 in.
	Height	750mm – 850mm	29-1/2–33-1/2 in.
	Depth	550mm	21-5/8 in.
Machine Weight		75kg	167 lbs.
Table Height		750, 770, 790, 810, 830, 850mm	29-1/2, 30-3/8, 31-1/8, 31-7/8, 32-5/8, 33-1/2 in.
Package Size	Min	W90 × H30	W 3-1/2x H1-1/8 in.
	Max	Free	
Tension		3 – 35 kgf (29.4 – 343N)	
Strap Width		5, 6, 9, 12, 15.5mm	1/4, 3/8, 1/2, 5/8 in.
Sealing Method		heat sealed	
Power Supply		100, 110, 120, 220, 230, 240v Single Phase 50/60Hz 0.56KVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

Pats., U.M. & design registered and/or pending.

© 2001 Strapack Corporation

DISTRIBUTED BY:

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

STRAPACK CORPORATION

1-2-17, Higashi Shinbashi, Minato-ku, Tokyo 105-0021, JAPAN
Phone 81-3-3289-1161 Fax. 81-3-3289-1160
(URL) <http://www.strapack.com>
(E-mail) info@strapack.com

STRAPACK INC.

30860 San Clemente St. Hayward, CA 94544 U.S.A.
Phone 1-510-475-6000 Fax. 1-510-475-6090

