

Call Allstrap (866) 779-2673

P328

**Battery powered plastic strapping tool
for general strapping applications**



**Strapping tool for strapping widths up to 16 mm/5/8"
and with a tension force up to 2600 N/585 lbs.**

Call Allstrap (866) 779-2673

P328

Battery powered plastic strapping tools

The new tool model P328 is available as a **one-button tool** as well as a **two-button tool** for all strapping dimensions. The one-button tool is operating **automatically**. Just by tipping the electrical push-button the process starts. The new tool operates also with a **new brushless motor**. This state-of-the art technology results in less maintenance and longer life time of the motor.



Advantages:

- Tension force up to 2600 N / 585 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single) button version available
- Brushless motor for less maintenance and improved life time
- Improved plate and guides - less effort to remove the tool from the strap
- No tension rocker - easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating

Characteristics

Strapping qualities:		PET plain and embossed
Strapping dimensions:	widths	12.0 - 16.0 mm / 7/16 - 5/8"
	thicknesses	0.40 - 1.05 mm / .016 - .041"
Weight:		4.3 kg / 9.6 lbs (including 4.0 Ah battery)
Dimension:		L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6"
Average seal strength:		approx. 75 % (dependent on strap quality)
Tension force:		250 - 2600 N / 56 - 585 lbs (adjustable)
Tensioning speed:		67 - 124 mm/s / 2.6 - 4.9 inch/s
Power supply:		Battery 18VDC / 4.0Ah Li-Ion

P328



Semi-automatic version



Automatic version

