

CALL ALLSTRAP 1-866-779-2673

P329

**Battery powered plastic strapping tool
for demanding applications**



**Powerful tool for strapping widths up to 19 mm/³/₄"
and with a tension force up to 4000 N/900 lbs.**

CALL ALLSTRAP 1-866-779-2673

P329

Battery powered plastic strapping tools for demanding applications

The new tool model P329 is available as a **one-button tool** as well as a **two-button tool** for all strapping dimensions. The one-button tool is operating **automatically**. Just by tipping the electrical push-button the process starts. The new tool operates also with a **new brushless motor**. This state-of-the art technology results in less maintenance and longer life time of the motor.

Advantages:

- High tension force up to 4000 N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single) button version available
- Brushless motor for less maintenance and improved life time
- Improved plate and guides - less effort to remove the tool from the strap
- No tension rocker - easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating



Characteristics

Strapping qualities:		PET plain and embossed
Strapping dimensions:	widths	16.0 - 19.0 mm / 5/8 - 3/4"
	thicknesses	0.65 - 1.35 mm / .026 - .053"
Weight:		4.3 kg / 9.6 lbs (including 4.0 Ah battery)
Dimension:		L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6"
Average seal strength:		approx. 75 % (dependent on strap quality)
Tension force:		500 - 4000 N / 112 - 900 lbs (adjustable)
Tensioning speed:		49 - 79 mm/s / 1.9 - 3.1 inch/s
Power supply:		Battery 18VDC / 4.0Ah Li-Ion

P329



Semi-automatic version



Automatic version

