

StrapPack[®]

Automatic Side-Seal Model



RQ-8Y

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

RQ-8Y

Side-Seal Model



FAST!

1.7 seconds per strap (equivalent to 35 straps per minute).

ADAPTS EASILY TO AUTOMATED PACKAGING LINES

The machine fits any existing or proposed conveyor system without modification, adapts to any conveyor height and requires no special equipment.

WIDE ADAPTABILITY TO FULLY-AUTOMATED PACKAGING LINES

End-of-cycle and strapping error signals are available as options. Larger arch sizes offer a wide range of applications, particularly for large and heavy packages.

EASY STRAP LOADING

No complicated strap threading. It only requires a touch of the outside lever.

VARIABLE TENSION

A single dial provides a wide range of tension for all packages. Tension adjustable up to 80kg (175lbs.), equivalent to 150mm (6 inch) stroke.

QUICK HEATER

In less than 25 seconds, operating temperature is reached.

EMPTY STRAP COIL DETECTION

Operation automatically stops when the strap coil is empty plus an optional warning signal is available. Easy removal of any excess strap ensures uninterrupted operation.

RE-FEED FUNCTION


Features automatic resetting of the machine for continuous operation even if a strap forwarding failure were to occur.

AUTOMATIC STRAP EJECTION

If a strap cycle is accidentally started without a package, empty strap loops are automatically ejected and all functions are reset for the next cycle.

SELF-DIAGNOSTIC MECHANISM

A programmable microprocessor constantly monitors critical functions — any irregularity detected is immediately displayed.



Standard Specifications

Dimensions	Width	1500mm	59-1/8 in.
	Height	1722mm	67-13/16 in.
	Depth	610mm	24 in.
	Weight	200kg	440 lbs.
Arch Size		W 600 × H 850mm	W 23 × H 33 in.
Package Size	Max	W 570 × H 820mm	W 22-1/2 × H 32-5/16 in.
	Min	W 30 × H 100mm	W 1-1/4 × H 4 in.
Joint / Strap / Coil		heat seal / polypropylene / ID 200 × OD 450 × W 200mm	heat seal / polypropylene / ID 8 × OD 18 × W 8 in.
Strap Width		5, 6, 9, 12mm	1/4, 3/8, 1/2 in.
Strap Tension		Max. 80kg 150mm stroke	Max. 176 lbs. 6 in. stroke
Speed		1.7 sec./strap 35 straps per min.	
Power Supply		110, 120, 200, 220, 230, 240V 1 phase 50 / 60Hz 0.65KVA	

Arch Size Chart

H \ W	400 (16)	500 (20)	600 (24)	800 (31)	1000 (39)
650 (25)					
850 (33)			STD		
1050 (41)					
1250 (49)					
1450 (57)					

Sizes in millimeters / (inches).