



M. J. MAILLIS GROUP

ST-INCA 10-13

P N E U M A T I C S E A L L E S S T O O L



- Lightweight and compact
- Ergonomic and elegant design
- Fast and easy operation
- Suitable for high tensile strapping
- Sealless joint - reduced overall strapping costs

Technical data	
Strap quality	Standard / High Tensile
Joint type	sealless
Package type	flat
Strap width	10-13 / 3/8" - 12"
Strap thickness / Standard Strap	0,4-0,6 mm./ .015" - .023"
Strap thickness / High Tensile Strap	0,4-0,5 mm./ .015" - .020"
Max. tension	3.000 N / 306 kg
Max. tension speed	11 m/min
Air pressure	6/7 bar
Air consumption	9 lt/sec
Weight	6,5 kg / 14,30 lbs

www.gripa.it (Cristallo B. - M)

Chart of types				
MODEL	ITEM.NO.	STRAP WIDTH	MAX TENSION N	TENSION SPEED (m/min)
ST-INCA 10	105.100.310	10 mm. 3/8"	2.000	11
ST-INCA 10	105.100.410	10 mm. 3/8"	3.000	7
ST-INCA 13	105.130.310	13 mm. 1/2"	2.000	11
ST-INCA 13	105.130.410	13 mm. 1/2"	3.000	7

FEATURES AND BENEFITS

- ST INCA is a lightweight, compact pneumatic sealless strapping tool, ideal for flat packages. The sealless joint reduces the overall strapping costs.
- Equipped with two buttons and an innovative hydraulic system which prevents the loss of oil. Allows an efficient, fast and reliable operation.
 - High and consistent joint efficiency.
 - Suspension bracket allows the use in a wide variety of standard - horizontal - vertical applications.
- Strap tension can be easily and quickly regulated.



Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212

