

The only available manual sealless combination tools for 1 1/4" (32 mm) wide steel strapping, with an easy to use reverse locking system. Our exclusive "Z-Lock" reverse locking system is designed for the most demanding applications. It provides added protection against the loosening or unlocking of the sealless connection in either direction.

These tools are designed for the strapping of concrete products, crates, lumber, metal products, palletized products as well as other products to be unitized with steel strapping.

The ZL90 series tools are specifically designed for use with **high tensile steel strapping** (of up to 156,000 psi / 1100 N/mm²) and may also be used with regular duty strapping for much improved durability. For use with strapping sizes from 1 $1/4 \times .025$ " (32 mm x 0.635 mm) to 1 1/4" x .031" (32 mm x 0.80 mm).

The proven patented design provides optimal seal joint efficiency, while at the same time requiring minimal effort for a tool in this category.

Manufactured to use the fewest individual parts and components, less maintenance and repair is required.

Replacement of parts is very simple and it takes only a few minutes to replace the feedwheel, gripper, knife, punch or die.

Distributed By:

Manufactured from only the most durable materials, this tool provides

1719 Kenny Rd Columbus, OH, 43212

Allstrap

unsurpassed reliability.

TECHNICAL SPECIFICATIONS

Model Number	Strap Width	Strap Thickness
ZL90-1	1 1/4" (32 mm)	.025"031" (0.635 mm - 0.80 mm)

Weight	13.4 lbs (6.0 kg)
Base Length	4.9" (125 mm)
Base Width	2.8" (70 mm)
Height	4.4" (110 mm)

Click here to Print

Email Us

Distributed By: **Allstrap**1719 Kenny Rd

Columbus, OH, 43212