

## **ZP26 "B " VERSION WITH BRUSHLESS MOTOR!!**





## **ZP26-6B** Battery powered. Automatic tension (330Kgs) plastic strapping tool

- "3 Year Warranty" on Brushless Motor and ECU (Electronic Control Unit)
- The most powerful tool for heavy duty strapping.
- Automatic tension, automatic friction weld sealing & cutting. No metal seals required.
- A protection shelter keeps tension & sealing adjustment knobs from undesired touch.
- Ergonomic design and excellent weight distribution reduce hand strength.
- Easy "One-Step" straps inserting.
- No strap slippery by over tension. No residue piled-up by improper releasing method.
- Computer controlled operation monitoring system.
- User self-adjustable front & rear strap width guiders assure perfect strap alignment.
- User changeable strap cutting blade and other wearing parts.
- 14.4V 3.0Ah Ni-MH high capacity rechargeable battery
- BOSCH 30 minutes charger.
- Optional hanger reduces operation fatigue.
- Specifications:
  - \*Suitable for polyester (PET) or Polypropylene (PP)
  - \*Strap width 13-16mm (4/8-5/8 inches)
  - \*Strap thickness: PET 0.60-1.27mm ( .024 .04 inches )

PP 0.75mm- 1.27mm ( .029- .04 inches )

- \*Maximum tension: 330 KGS (3300 N)
- \*Sealing efficiency: 85+-5%
- Max. strap thickness 1.27mm (0.05") is allowed. However, a changeover of blade (part no. 2885) is required

**ZP26-9B** is also available for 16 & 19 mm strap width (5/8 & 3/4 inches)

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212